

Commel LV-673 BIOS V1.4

CMOS-Setup changes

Start from “Load Optimized Defaults”

Changes made from Optimized defaults:

- Standard CMOS Setup:
 - o Drive A: ***NONE***
 - o Halt On: ***No Errors***
- Advanced CMOS Setup:
 - o First Boot Device: ***USB-CDROM***
 - o Second Boot Device: ***Disabled***
 - o Third Boot Device: ***Hard Disk***
 - o Boot up Floppy Seek: ***Disabled***
 - o Boot Up Numlock Status: ***OFF***
- Advanced Chipset Features:
 - o ***** VGA Settings *****
 - Boot Display: ***Dual***
 - LCD Type: ***2***
- Integrated Peripherals
 - o On Chip IDE
 - On Chip Secondary PCI IDE: ***Disabled***
 - On Chip Serial ATA: ***SATA Only***
 - o On Board Device
 - USB Keyboard Support: ***Enabled***
 - USB Mouse Support: ***Enabled***
 - o Super IO Device:
 - Onboard FDC Controller: ***Disabled***
 - Onboard Serial Port1: ***Disabled***
 - Onboard Serial Port2: ***Disabled***
 - PWRON After PWR-Fail: ***ON***
 - o Onboard Serial Port3: ***Disabled***
 - o Onboard Serial Port4: ***Disabled***